

PrimaTech has added the LL4B3 Series 8 Bolt Landing Gear Set with low profile sand shoes. We now offer the 8 bolt and the 10 bolt mounting for all standard duty applications. Both models are universal mount with several unique features that deliver excellent performance and durability.

Specifications

LL4B1/B3 Series - 8 Bolt

- 130,000 lb. Static Load Capacity
- 29,000 lb. Side Load Capacity
- 39,000 lb. Lift Capacity
- 17" Travel
- Direct Replacement for Austin CMR/CMS

LL5B1 Series - 10 Bolt

- 170,000 lb. Static Load Capacity
- 29,000 lb. Side Load Capacity
- 60,000 lb. Lift Capacity
- 17" Travel
- Comparable to KIC & Holland/Binkley 50,000



PN: LL4B1-7078

PN: LL4B3-7078

Full Set with hardware

(Cross shaft, handle, handle hook & two brace ears)

PN: LL4B1-7000

Set with two brace ears only

PN: LL4B1-7100

PN: LL4B3-7100

Non gear side only

PN: LL4B1-7200

PN: LL4B3-7200

Gear side only

Features/Benefits

- Powder coated finish for corrosion protection
- Zinc plated shafts for added durability
- Precision gear design for trouble free shifting
- Elevating nut with grease reservoir for lube retention
- Specially formulated grease protects from -40°F to 300°F for easy operation and reduced wear
- **LL4B1 & LL5B1 have standard sand shoes. LL4B3 have low profile sand shoes.**

Additional landing gear mounting components such as adjustable braces and bolt kit also available.



PN: LL5B1-7078

Full Set with hardware

(Cross shaft, handle, handle hook and two brace ears)

PN: LL5B1-7100

Non gear side only

PN: LL5B1-7200

Gear side only



PN: LGBK

5/8" x 1 1/2" bolts (10 each) with nylon insert lock nuts - used with 4 or 5 bolt legs

