

PrimaTech TES295 is a premium synthetic heavy duty universal power shift and automatic transmission oil suitable for use in transmissions requiring **Allison TES295** fluids. It is engineered to meet the requirements of the latest HD transmissions delivering ultimate performance in severe operating conditions. PrimaTech TES295 is available in 1 gallon, 5 gallon and 55 gallon drums.



PN: PTATF-TES295-G  
PTATF-TES295-5G  
PTATF-TES295-55G

## Features/Benefits

- **Excellent thermal and oxidation stability** - PrimaTech TES295 resists formation of deposits to ensure longer fluid life and better fluid performance under severe conditions.
- **High viscosity index** - PrimaTech TES295 incorporates the latest synthetic based oil technology, providing outstanding high and low temperature performance. Including extremely low temperature fluidity, further protecting the transmission components from premature wear under extreme operating conditions.
- **Excellent shear stability, corrosion and foaming resistance** - PrimaTech TES295 retains its fluid characteristics even under high loads and shear conditions. The excellent wear protection, shear stability and frictional characteristics of the additive technology provides outstanding oil performance allowing for extended oil drain intervals while maximizing the life of the transmission.
- **Compatible with most other automotive transmission fluids and seals** - When changing to PrimaTech TES295 it is recommended that the transmission system is appropriately drained and flushed in order to obtain all of the performance benefits that changing to this fluid will provide. However, PrimaTech TES295 is compatible with most other transmission fluids and seals.
- **One fluid for year-round use in all geographic locations**
- **Oil drain interval potential** - This technology allows extended oil drain intervals up to 50,000 miles for severe service and 100,000 miles in specific Allison transmissions. Oil analysis should be conducted in accordance with the transmission OEM requirements.
- **PrimaTech TES295 is tested per ASTM D-445, D-2270, D-287, D-92 and ISO 3016**

## Recommendations

- Allison TES-389 (AA-32332007)
- Former Dextron® III applications
- Former Ford Mercon® applications
- Ford Mercon® V (M5060501)
- Voith
- ZF TE-ML14B, 16L, 17C
- Allison C-4
- MAN 339 Type F

## Vehicle Types

- Municipal fleets
- Vans
- Buses, school buses, coaches
- Emergency vehicles
- Commercial vehicles and trucks
- Motor homes
- On/off highway vehicles
- Heavy duty pickup trucks