


PrimaTech SAE 15W40, is an exceptional universal or mixed fleet heavy duty engine oil, formulated to meet or exceed many industrial engine manufacturer requirements for diesel and gasoline engines operating in severe conditions in wide variations of climate conditions. PrimaTech 15W40 meets the latest API specification CJ-4 and is formulated to provide excellent performance in the new EGR (Exhaust Gas Recirculation) engines.

- Excellent protection from deposits at all operating temperatures
- Excellent bearing corrosion protection (EGR critical)
- Excellent anti-wear, anti-foam, and anti-rust properties
- Excellent soot control
- Extended drain capable



PrimaTech 15W40 may be recommended for the following uses:

- When CJ-4, CH-4, CI-4, CI-4 Plus, CG-4, CF-4, CF, CF-2, CE, CD-II oils are required
- When SM, SL, SJ, SH, SG, SF, SE, SD, SC oils are required
- When U.S. Military CID A-A-52306 performance level is required
- When MIL-Prf-2104G oils performance level is required
- In truck diesel engines, including turbo-charged models
- In gasoline engines
- When Caterpillar drive trains (TO-2) spec is required
- When Allison C-4 spec is required



PrimaTech 15W40 is certified by the American Petroleum Institute.

TYPICAL PROPERTIES	
Property	Typical
Gravity, API	29.0
Viscosity	
CST @ 40C	106.0
CST @ 100C	14.5
Viscosity Index	141.0
Pour Point: C	-32.0
Flash Point: C	231.0
Borderline Pumping: C	-20.0
Sulfated ASH wt%	1.2
TBN	10